

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11)Publication number: **61179269 A**

(43)Date of publication of
application: **11. 08 . 86**

(51)Int. Cl **C09D 11/00**

(21)Application number: **60018734**

(22)Date of filing: **04 . 02 . 85**

(71)Applicant: **CANON INC**

(72)Inventor: **IWATA KAZUO
KOIKE SHOJI**

(54)INK COMPOSITION FOR INK JET
RECORDING

(57)Abstract:

PURPOSE: To provide the titled compsn. which has excellent discharge stability, does not cause excessive blotting on woven or nonwoven fabric and can form fine pattern, consisting of a reactive dye and an aq. medium and having surface tension within a specified range.

CONSTITUTION: 0.1W15wt% reactive dye (e.g.

C.I. Reactive Yellow 2) and optionally additives such as dispersant, surfactant, viscosity modifier, anti-foaming agent, penetrant, mildewproofing agent, pH adjustor, etc. are dissolved or dispersed in an aq. medium composed of water alone or water and a water-soluble high-boiling org. solvent (e.g. ethylene glycol) to obtain an ink compsn. for ink jet recording, which has a surface tension of 35W60 dyne/cm at 25°C.

COPYRIGHT: (C)1986,JPO&Japio